

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

NO. OF COPIES RECEIVED	3
* DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

O. C. C.
ARTEBIA, OFFICE

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER

2. Name of Operator
Black River Corporation ✓

3. Address of Operator
620 Commercial Bank Tower, Midland, Texas 79701

4. Location of Well
UNIT LETTER B 860 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 29 TOWNSHIP 22 S RANGE 27 E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
BRC-Madera

9. Well No.
1

10. Field and Pool, or Wildcat
S. Carlsbad Morrow

15. Elevation (Show whether DF, RT, GR, etc.)
3138 .8 Ground Level

12. County
Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
SUBSEQUENT REPORT OF:

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

OTHER _____

PLUG AND ABANDON

CHANGE PLANS

OTHER _____

REMEDIAL WORK

COMMENCE DRILLING OPNS.

CASING TEST AND CEMENT JOBS

OTHER _____

ALTERING CASING

PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, SEE RULE 1103.

on 2-10-78 drilling continued with a 6 1/2" hole to a total depth of 11,842' and @ 5" O.D. S
18 # liner was hung in the following manner. 11,842'

1.50'	-	1 Baker Guide shoe
33.95	-	1 Jt. 5" OD SFJ - 18 # casing
1.58	-	1 Baker float collar
39.95	-	1 Jt. 5" OD SFJ - 18 # casing
1.00	-	1 TIW plug landing collar
695.47	-	18 Jts. 5" OD SFJ - 18# casing
12.00	-	1 TIW J slot liner hanger with packer
<u>785.45</u>		

Plug landed in collar at 11,765.02. Cemented with 110 sacks class H cement with 3/4 of 1# friction reducer. Bumped plug - set packer and hold down. Displaced hole with 5% KCL water.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ronnie Sanders TITLE Vice President DATE 3-13-78

APPROVED BY W. A. Grosse TITLE SUPERVISOR, DISTRICT U DATE MAR 29 1978

CONDITIONS OF APPROVAL, IF ANY: