

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Belec Petroleum Corp.</u>		Lease <u>Walker Coleman</u>		Well # <u>1</u>	
Location of Well	Unit <u>B</u> <u>3300</u> <u>2300e</u>	Section <u>29</u>	Township <u>22</u>	Range <u>27</u>	County <u>El Paso</u>
Drilling Contractor			Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM 6-13-78

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 5/8"</u>	<u>24</u>		<u>400</u>	<u>200 ccs.</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5</u>		<u>3400</u>	<u>700</u>

Casing Data:

Surface _____ joints of 8 5/8 inch 24 # Grade K-55

(Approved) (Rejected)

Inspected by Mike Stufflefield date 9/17/78

Cementing Program

Size of hole 11" Size of Casing 8 5/8 Sacks cement required 250

Type of Shoe used guide Float collar used none Btm 3 jts welded yes

TD of hole 401' Set 401' Feet of 8 5/8 Inch 24 # Grade K-55

New-used csg. @ 401' with 250 sacks neat cement around shoe

+ _____ sack _____ additives

Plug down @ 4030 (AM) (PM) Date 9/8/78

Cement circulated 025 No. of Sacks 16

Cemented by D. Wall Witnessed by Mike Stufflefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: 3 centralizer @ 400' - 360' - 320'