

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION  
MAY 19 1980

O. C. D.  
ARTESIA OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Dry</b>	7. Unit Agreement Name
2. Name of Operator <b>The Eastland Oil Company</b>	8. Farm or Lease Name <b>C. R. Lopez "D"</b>
3. Address of Operator <b>P.O. Drawer 3488, Midland, Texas 79702</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>N</b> <b>330</b> FEET FROM THE <b>South</b> LINE AND <b>1980</b> FEET FROM THE <b>West</b> LINE, SECTION <b>29</b> TOWNSHIP <b>22S</b> RANGE <b>28E</b> NMPM.	10. Field and Pool, or Wildcat <b>Herradura Bend - Cherry Canyon</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3019' GR</b>	12. County <b>Eddy</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

C. R. Lopez "D" #1 was drilled to 2493 feet on March 15, 1979 using a cable tool rig. Work was begun on April 28, 1980 to deepen to the Cherry Canyon Sand using a reverse rig. Total depth of 3330 feet was reached May 10, 1980. After running Schlumberger logs, no productive zones were found in the Well. Surface casing consisting of 24#, 8 5/8" had been set at 376 feet with cement circulated to surface. It is proposed to plug the well by setting cement plugs as follows: 35 sacks - 3300 to 3200', 35 sacks - 2525 to 2425', 35 sacks - 2200 to 2100', 35 sacks - 425 to 325', 15 sacks at surface. No casing will be recovered and the hole will be loaded with 10 ppg mud and plugs spotted through 2 1/2" tubing. Plugging operations are to begin at 8:30 AM May 13, 1980.

(Verbal approval for plugging obtained from Mr. W. A. Gressett of the Artesia Office)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *George P. Hual* TITLE Superintendent DATE May 14, 1980

APPROVED BY *W. A. Gressett* TITLE SUPERVISOR, DISTRICT II DATE MAY 20 1980

CONDITIONS OF APPROVAL, IF ANY: