

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert Depth	R E C T A N G U L A R C O O R D I N A T E S	Dogleg Deg/100ft	Vert Sect
0.00	0.00	0.00	0.00	0.00 E	0.00	0.00
100.00	0.49	266.04	100.00	0.43 W	0.49	-0.43
200.00	0.47	261.09	200.00	1.26 W	0.04	-1.26
300.00	0.37	285.02	299.99	1.98 W	0.20	-1.98
400.00	0.61	275.36	399.99	2.82 W	0.25	-2.82
500.00	0.50	265.20	499.98	3.79 W	0.14	-3.79
600.00	0.43	284.14	599.98	4.58 W	0.17	-4.58
700.00	0.43	291.77	699.98	5.30 W	0.06	-5.30
800.00	0.60	274.26	799.97	6.17 W	0.23	-6.17
900.00	0.40	271.11	899.97	7.03 W	0.20	-7.03
1000.00	0.48	265.00	999.97	7.80 W	0.10	-7.80
1100.00	0.29	269.88	1099.97	8.47 W	0.20	-8.47
1200.00	0.33	295.00	1199.96	8.98 W	0.14	-8.98
1300.00	0.31	261.41	1299.96	9.51 W	0.18	-9.51
1400.00	0.32	262.92	1399.96	10.05 W	0.02	-10.05
1500.00	0.32	249.50	1499.96	10.60 W	0.08	-10.60
1600.00	0.18	255.29	1599.96	11.01 W	0.14	-11.01
1700.00	0.20	128.67	1699.96	11.03 W	0.34	-11.03
1800.00	0.27	88.08	1799.96	10.66 W	0.17	-10.66
1900.00	0.56	106.95	1899.95	9.96 W	0.32	-9.96
2000.00	0.70	103.43	1999.95	8.90 W	0.15	-8.90
2100.00	0.58	93.26	2099.94	7.80 W	0.17	-7.80
2200.00	0.68	111.01	2199.94	6.74 W	0.22	-6.74
2300.00	0.63	102.15	2299.93	5.65 W	0.11	-5.65
2400.00	0.40	125.31	2399.93	4.84 W	0.30	-4.84

All data is in feet unless otherwise stated.
Coordinates from slot #1 and TVD from rotary table.
Bottom hole distance is 1150.22 on azimuth 94.24 degrees from wellhead.
Vertical section is from N 0.00 E 0.00 on azimuth 90.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ