

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

SEP 04 '90

WELL API NO.
30-015-22889

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-3346

7. Lease Name or Unit Agreement Name

Loving AIB State

8. Well No.
1

9. Pool name or Wildcat
South Loving Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER RE-ENTRY

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter G : 1550 Feet From The North Line and 1780 Feet From The East Line

Section 16 Township 23S Range 28E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3024.1' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud re-entry, perforate, treat ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-24-90. Spudded 1:30 AM 8-24-90. Drilled to 380' and stringer to 427'. Tested perms at 400' to 1000', OK. TIH. Tagged cement at 2506'. Drilled retainer 2595-97' and cement to 2772'. Tested perms at 2700' to 1000', OK. Drilled cement plug 5367-5480'. Washed to CIBP at 5880'. Drilled and pushed to 6023'. Set cement retainer at 5853'. Squeezed perms 5938-75' w/75 sx Class H w/.2% CF-1 and 50 sx H Neat to 1200# w/110 sx in formation. Reverse out POH. WOC. 8-28-90. Drill retainer at 5853' and cement to 5990'. Tested to 400# with no bleed off. Drill remainder of CIBP at 6023' and retainer at 6050'. Worked bottom of retainer to 6251'. Unable to go deeper. TIH with bit and scraper to 6251'. Could not push junk retainer any further. Circulated hole w/2% KCL and POOH. TIH with packer and set at 6150'. Tested PBTD to 2500#, OK. 8-30-90. Perforated w/28 - .40" holes as follows: 6070-76' (2 SPF-13 holes), 6080' (2 holes), 6084-91' (2 SPF-13 holes). Acidized perms w/2500 gals acid.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 8-31-90

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE SEP 6 1990

CONDITIONS OF APPROVAL, IF ANY: _____