

WELL SCHEMATIC

Pardue "34" Well No. 1
API #30-015-22902
UL H, 2310' FNL, 660' FEL
Section 34 T-23-S R-28-E
Eddy County, New Mexico

Casing, 13.375", @ 0-516', TOC @ surface

Casing, 9.625", @ 0-2550', TOC @ surface

Top of 7" casing, cut @ 4800'

Cement plug #5 in casing @ 4995-5413'

Junk in 7" casing @ 5413-5969'

Top of 7" cement @ 5600' by bond log

Delaware perfs @ 6056-6165'

Bridge plug in 7" casing @ 6200'

Delaware perfs @ 6214-6245'

Bridge plug & cement in casing @ 6310-6360'

Bone Spring perfs @ 6370-6408'

Cement plug in casing @ 7000-7150'

Cement plug in casing @ 9425-9575'

Cement plug in casing @ 10,800-11,023'

Casing, 7", @ 4800-11,236', TOC @ 5600'

Atoka perfs @ 11,756-11,772', cemented off

Casing liner, 4.5", @ 11,024-13,050'

Total depth of well @ 13,050'

8.5" open hole

Sidetracked 7.875" open hole
@ 4498-6350'

Casing, 5.5", 15.5 & 17#, @ 0-6348'
TOC @ approx. 4000'

Proposed completion interval

Total depth (8/2000) 6350'

