

IF NEEDED FRAC AS FOLLOWS:

4. BJ-TITAN FRAC ATOKA PERFS (12,730-12,737) W/6500 GALS TERRA FRAC T-5*
W/10,000# 20/40 SINTERED BAUXITE AS FOLLOWS:
- A) PUMP 3000 GALS TERRA FRAC (TFT5) PAD
 - B) PUMP 500 GALS TERRA FRAC (TFT5) W/1 PPG 20/40 SINTERED BAUXITE.
 - C) PUMP 500 GALS TERRA FRAC (TFT5) W/2 PPG 20/40 SINTERED BAUXITE.
 - D) PUMP 1500 GALS TERRA FRAC (TFT5) W/3 20/40 SINTERED BAUXITE.
 - E) PUMP 1000 GALS TERRA FRAC (TFT5) W/4 PPG 20/40 SINTERED BAUXITE.

PUMP @ 7 BPM. MAX WHTP-8,000 PSI.

5. FLOW WELL BACK FOR CLEAN-UP & TEST.

* FRAC FLUID ADDITIVES:

KCL	167 PPT		
GW-32	50 PPT	GEL	CLATROL-6 2GPT CLAY CONTROL
NE-13	2 GPT	NON-EMULSIFIER	INFLO-50 1GPT SURFACE TENSION REDUCER
XLW-42	1.5 GPT	CROSSLINER	
GBW-5	.5 PPT	BREAKER	
BF-3	10 PPT	BUFFER	