

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

SEP 20 11 42 AM '90

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
RB Operating Company

SEP 27 '90

3. ADDRESS OF OPERATOR
2412 N. Grandview, Suite 201, Odessa, Tex. 79761

C. C. D.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980 FSL & 990FEL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☒
☐
☐
☐
☐
☐

(other) Plug back, Perforate, & Cement Squeeze

5. LEASE

NM 32636

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Amoco Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

E. Loving (Delaware)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 11- T23S - R28E

12. COUNTY OR PARISH

Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

2992.1 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/11/90 Set CIBP in tubing at 11354'. Cut off tubing @ 11342'.
9/12/90 Set 200 sx cement plug 11292'-10464'. Omission of cement plug from 9910-9810 was approved by Shannon J. Shaw per telephone on 9/18/90.
9/13/90 Set CIBP @ 6350'. Ran CBL.
9/14/90 Perforated squeeze holes 6078-80 & 6290-92. Established circulation. Set cement retainer @ 6260'.
9/15/90 Squeeze perfs 6290-92 with 200 sx cement.
9/16/90 Squeeze perfs 6078-80 with 200 sx cement.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James G. Stewart TITLE Engineer DATE 9/18/90

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: