

UNITED STATES *Artesia, NM 88210*
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. Oil ☐ well Gas ☒ well other ☐
2. NAME OF OPERATOR
Harvey E. Yates Company
3. ADDRESS OF OPERATOR
P. C. Box 1933, Roswell, New Mexico 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2280' FSL & 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☐
FRACTURE TREAT ☐	☐
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☒	☒
(other) ☐	☐

5. LEASE
NM-22064
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME *RECEIVED*
8. FARM OR LEASE NAME *DEC 2 1982*
Last Chance
9. WELL NO. *O. C. D.*
1
10. FIELD OR WILDCAT NAME
Wildcat *Artesia, OFFICE*
11. SEC, T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28, T-23S, R-24E
12. COUNTY OR PARISH 13. STATE
Eddy NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3929.66'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/19/80 Rel pkr, POH w/tbg & pkr. RIH & set CIBP @ 6550' & 35' cmt on top. FBTD @ 6515'.

11/20/80 RIH w/jet casing cutter & cut pipe @ 6180'.

11/21/80 RU csg jacks, pulled & LD 150 jts - 5 1/2" 17 lb/ft LT&C csg.

11/24/80 Ran tbg in hole to 6255' (75' inside of 5 1/2" csg stub) mixed 40 sx C1 "H" cmt & spotted 175' plug @ 6255'. Pulled 15 stds tbg. SD @ 12:30 p.m. WOC.

11/28/80 WOC 96 hrs. Ran tbg in hole, tagged top of plug @ 6090' (165' plug). Pulled & LD 114 jts tbg to 2798'. Mixed & spotted 100' cmt plug from 2798' to 2698' (50' in & out of 8 5/8" csg @ 2730'. PD @ 11:45 a.m. 11/28/80. Pulled & LD 86 jts tbg. ND BOP, removed csg head & csg spool. Mixed 10 sxs cmt surface plug. Welded steel plate across 13 3/8" OD csg stub. Installed DH marker. P & A @ 4:00 p. m. 11/28/80.

Subsurface Safety Valve: Model and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Peter W. Chester

TITLE

Engineer

DATE October 15, 1982

APPROVED BY
CONDITIONS OF APPROVAL, IF ANYAPPROVED
(Orig. Sgd.) PETER W. CHESTER

NOV 30 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

Instructions on Reverse Side

DATE

RECEIVED

OCT 16 1982

MINERALS INDUSTRY SERVICE