N.M.O.C.D. COPY

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

5. LEASE NM 75953

		<u>/// </u>		/	<u> </u>	1.	<u> </u>	_	
5.	IF INDIAN,	ALLOT	TEE	OR	TR	IBE	NA	ME	
							,		

DEPARTMENT OF THE INTERIOR						
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME					
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug packets at the eservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME					
eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME					
1. oil gas v	Federal AI Com.					
well well other AUG 7 1980	9. WELL NO.					
2. NAME OF OPERATOR Amoco Production Company O. C. D.	10. FIELD OR WILDCAT NAME					
3. ADDRESS OF OPERATOR ARTESIA, OFFICE	Wildcat Morrow 11. SEC., T., R., M., OR BLK. AND SURVEY OR					
P. O. Box 68 Hobbs, NM 88240						
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 34-24-28					
below.)	12. COUNTY OR PARISH 13. STATE					
AT SURFACE: 1980' FSL & 1980' FEL	Eddy NM ~					
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4) AT TOTAL DEPTH:	14. API NO.					
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,						
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)					
	3006.9 GR					
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:						
TEST WATER SHUT-OFF	• • • • • • • • • • • • • • • • • • •					
FRACTURE TREAT SHOOT OR ACIDIZE						
REPAIR WELL	(NOTE: Report results of multiple completion or zone					
PULL OR ALTER CASING	change on Form 9–330.)					
MULTIPLE COMPLETE	9)					
CHANGE ZONES						
ABANDON* (other) ACTION						
·	in the details and give portingnt dates					
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly star including estimated date of starting any proposed work. If well is concluding estimated date of starting any proposed work.	te all pertinent details, and give pertinent dutes, directionally drilled, give subsurface locations and					
measured and true vertical depths for all markers and zones pertine	nt to this work.)*					
Drilled to a TD of 9900' and ran 40# N-80 9-	5/8" casing set at 9900'					
Cemented with 2760 SX Lite cement and 300 SX	Class H cement. Plugged down					
at 4:00 p.m. 7-24-80. Ran temp. survey. T	op of cement at approx. 2930'.					
WOC 18 hr. Test casing with 1500# for 30 mi	n Test OK Reduced hole					
	II. 1630 OK. Reduced note					
to 8-1/2" and resumed drilling.						
0+4-USGS, A 1-Hou 1-Susp 1	-LBG					
1-Pecos Irr. 1-HNG 1-Union Oil o	of CA. 1-R. Enfield					
	**					
Subsurface Safety Valve: Manu. and Type	Set @ Ff					
18. I hereby certify that the foregoing is true and correct						
SIGNED BOG NOWID TITLE Admin. Analy	St DATE					
V. V						

(This space for Federal or State office use)

DATE

ACCEPTED FOR RECORD

AUG 5 1980

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

*See Instructions on Reverse Side