

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator AMINOIL USA, INC.	8. Farm or Lease Name Kirkes
3. Address of Operator 601 N. Loraine, Midland, TX 79701	9. Well No. 1
4. Location of Well UNIT LETTER J 2080 FEET FROM THE south LINE AND 1773 FEET FROM THE east LINE, SECTION 10 TOWNSHIP 24S RANGE 28E N.M.P.M.	10. Field and Pool, or Wildcat Undes. Malaga Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3003' G.L.	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER Perforating ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 7- 1-80 (12,000' TD) Drlg. cmt. @ 8893'
- 7- 2-80 Test csg. to 1500 psi - OK
- 7- 3-80 Tested pipe rams, blind rams, choke manifold & valves, kelly cock & safety valves to 10,000 psi, Hydril to 3000 psi.
- 7- 5-80 Drill cmt. & shoe, drill out 7-5/8" shoe @ 11:30 a.m., drlg. ahead.
- 7-10-80 Drlg. 12,278'. Run dev. @ 12,270' 2°.
- 7-17-80 Drilled to 12,800' TD.
- 7-18-80 Circ. & cond. hole to run 4 1/2" liner.
- 7-19-80 Running 4 1/2" from 11,684' - 12,799'. Ran 1115' of 4 1/2", 12.6#/ft. SFJ-Hydril. Cmt. w/170 sks. Class "H" - 50/50 Poz - 2% Gel - 4/10% Halad 22 - 4/10% CFR2 - 5# KCl/sk.
- 7-20-80 Circ. & cmt. 4 1/2" liner. Circ. & W.O.C.
- 7-22-80 Drill cmt. to 12,756'.

(Continued on following pages)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry L. Harper TITLE Operations Superintendent DATE 3/31/81
Jerry L. Harper
APPROVED BY W. C. G. Scott TITLE SUPERVISOR, DISTRICT II DATE APR 07 1981
CONDITIONS OF APPROVAL, IF ANY: