

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

452

DUNDRY NOTICES AND REPORTS ON WELLS

(Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. WELL TYPE ☐ OIL WELL ☐ GAS WELL ☐ OTHER Plug & Abandon

2. NAME OF OPERATOR

Nearburg Producing Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 31405, Dallas, Texas 75231-0405

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FWL

15. PERMIT NO.

16. FERTILITY (Show whether oil, gas, etc.)

4,168.4' GR

14.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

ACTIVITY

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

XX

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

02/11/90 Spudded well @ 3:00 PM (MST), 2/11/90. Drilled 17-1/2" hole to 356'.

02/13/90 Ran 8 jts (360.35') of 13-3/8", 48# casing. Cemented w/150 sx Premium
Plus Thick-Set. WOC 18 hrs. Tested casing to 1500# for 30 minutes -
held OK. Drilled 11" hole to 2537'.

02/18/90 Ran 78 jts (2542.66') of 8-5/8" casing, 24#. Cemented w/150 sx Thick-Set
10# Gilsonite, w/2% CaCl₂; 870 sx Howco Lite, 10# Gilsonite w/2% CaCl₂;
250 sx Class "C" w/2% CaCl₂ (total 1270 sx). Tagged cement @ 849' w/1".
Cemented to surface w/1". Tested casing to 1000# for 30 minutes - held
OK. Drill 7-7/8" hole to 9840' TD.

ACCEPTED FOR RECORD

MAR 10 1990

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Nichelle Byrum

TITLE

Production Secretary

DATE

3/27/90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side