Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department



DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

WELL API NO. 30-015-26304 5. Indicate Type of Lease

P.O. Box 2088 Santa Fe, New Mexico 87504-2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 FEE _ STATE X DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. K-3271 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: James A WELL [X] OTHER 2. Name of Operator Well No. Phillips Petroleum Company 3. Address of Operator 9. Pool name or Wildcat Cabin Lake (Delaware) 4001 Penbrook Street, Odessa, TX 79762 4. Well Location Line and 660 1650 Feet From The North East Н Line Unit Letter Feet From The Township 22-S Eddy 2 30-E uhip 22-S
Range 30-E

10. Elevation (Show whether DF, RKB, RT, GR, etc.) **NMPM** Section County 3220'GL; 3228'KB Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** PLUG AND ABANDONMENT **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: Set CIBP & acidized OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 12-13-93 - Pull sucker rod pump and rods. POOH w/production tubing. 12-14-93 - GIH w/5-1/2" Cast Iron Bridge plug to depth of 7050'. Set cast iron bridge plug and COOH. Set pkr. and test cast iron bridge plug to 1,000# Test O.K. Release pkr. and pull uphole to 6350' and set pkr. Treated the Delaware perfs. 6414'-6452' w/1,000 gals of Xylene. 12-15-93 - Remove pkr. from tubing. WIH w/prod. tubing 6341' of 2-7/8", J-55 Tubing (198 jts.) Tubing anchor set at 6543' in 15,000# tension. S/N at 6543'. Remove BOP. Install wellhead. WIH w/pump and rod string. Place well on test. 01-05-94 - Well pumped 145 bbls of water and 49.5 bbls of oil w/68 MSCF of gas in is true and complete to the best of my knowledge and belief. I hereby certify that the infogration ab-Supv.Regulatory Affairs DATE 01-18-94 (915) TELEPHONE NO. 368-1488 L. M. Sanders TYPE OR PRINT NAME

TITLE

(This space for State Use)

SUPERVISOR, DISTRICT !!

JAN 2 7 1994

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY