Submit 3 Copies to Appropriate District Office

State of New Mexico _...rgy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO.

P.O. Box 2088 RECEIVED Santa Fe, New Mexico 87504-2088 30-015-26542 DISTRICTII 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEB - 6 1991 STATEXX FEE L DISTRICT III 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 O. C. D. **VB-55** ARTESIA, OFFICE SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: GAS WELL XX Amethyst State Com WELL OTHER 2. Name of Operator 8. Well No. Nearburg Producing Company 9. Pool name or Wildcat 3. Address of Operator O. Box 823085, Dallas, Texas 75382-3085 <u> Undesignated Rustler Bluff</u> 4. Well Location 1,880 Feet From The north Feet From The Line and Line 32 24S Eddy **NMPM** County Section Township Range 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 2,903.3' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON **ALTERING CASING** REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **TEMPORARILY ABANDON CHANGE PLANS** CASING TEST AND CEMENT JOB **PULL OR ALTER CASING** OTHER: OTHER:_ 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 12/01/90 Spudded well @ 5:00 pm (MST). Drilled 17-1/2" hole to 600'. Ran 600' (14 jts), 48#, K-55, ST&C casing. Cemented w/650 sx 12/02/90 Class C Neat w/2% CaCl. Circulated 50 sx cement to pit. Tested casing and shoe to 1,000 psi for 30 minutes. 12/03/90 12/08/90 Drilled 12-1/4" hole to 2,808'. Ran 2,808' (65 jts) of 9-5/8" 40#, K-55, ST&C casing. Cemented w/1,125 sx Pacesetter Lite w/1/4# Cello-Seal and 100 sx Class C Neat w/2% CaCl2. 100 sx to pit. Test casing and shoe to 1,500 psi for 30 minutes. 12/09/90 12/22/90 Ran open hole logs. I hereby certify that the information above is true and complete to the best of my knowledge and belief. Production Secretary DATE 1/25/91 TTILE TELEPHONE NO. 214/739-177 TYPEORPRINTNAME Machelle Byrum

- TITLE -

(This space for State Use) ORIGINAL SIGNED, BY

MIKE WILLIAMS

SUPERVISOR DISTRICT If

7 1991

CONDITIONS OF APPROVAL, IF ANY: