	U. FED STATES PARTMENT OF THE INTER BUREAU OF LAND MANAGEMEN		Hodfi NH060	lonwell District  Led Form No.  -3160-4  DESIGNATION AND SER  5417	C S I	
Use "	NOTICES AND REPORTS  or proposals to drill or to deepen or plug "APPLICATION FOR PERMIT" for such y	ON WELLS back to a different reservoir.	_ 1	AN, ALLOTTER OR TRIE	BE NAME	
OIL, GAN WELL OTHER				7. UNIT AGREEMENT NAME		
YATES PETROLEUM (	CORPORATION	3a. Area Code & Phone 505/748-1471		LEASE NAME		
3. ADDRESS OF OPERATOR	Antonia NV 00000	1 303/ /40-14/1	9. WELL NO	AIK Federal		
4. LOCATION OF WELL (Report In See hiso space 17 below.)	o, Artesia, NM 88210 ocation clearly and in accordance with any	State requirementa.	1 1			
At surface		<b>,</b>		ington Ridge		
330' FSL & 430' FEL	, Sec. 11-22S-31E		11. SEC., T.	H., M., OR BLK. AND	Delawal	
14. PERMIT NO.			Unit P	, Sec. 11-T2	2S-R31E	
30-015-26549	15. ELEVATIONS (Show whether DE	, RT, GR, etc.)		OR PARISH 13. STA	TE	
	3566' GR		Eddy	NM		
Che Norter o	eck Appropriate Box To Indicate N	ature of Notice, Report, o	or Other Data			
TEST WATER SHUT-OFF	1	នៈវាគរ	SEQUENT AMPORT (	r:		
PRACTURE TREAT	MULTIPLE COMPLETE	WATER SHOT-OFF	X	EPAIRING WELL,		
SHOOT OR ACIDIZE	ABANDON*	PRACTURE TREATMENT SHOOTING OR ACIDIZING	! {	LTERING CASING		
(Other)	CHANGE PLANS	(Other)			-	
7. DESCRIBE PROPOSED OR COMPLE proposed work. If well is nent to this work.) *	TED OPERATIONS (Clearly state all pertinent directionally drilled, give subsurface locati	(Nors: Report res Completion or Reco details, and give pertinent da	ambierron melbill #	ad Log form )		
			actions 101 f	markers and gones	a perti-	
Spudded 26" hole 8:4 surface with redi-mand hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril si for 30 minutes, OK. Reserved.	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to dead drilling of Guide shoe so coseal(yield of the grant of the gran	to 17½" set 1.32,	
Spudded 26" hole 8:4 surface with redi-mand hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of the drilling of the seal (yield of the drilling).  ARECO ELECTRICATE OF THE SEAL OF	perti- to 17½" set 1.32,	
Spudded 26" hole 8:4 surface with redi-mand hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of the drilling of the seal (yield of the drilling).  ARECO ELECTRICATE OF THE SEAL OF	perti- to 17½" set 1.32,	
Spudded 26" hole 8:4 surface with redi-mand hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of the drilling of the drilling of the drilling of the drilling.  ARECA STATE OF THE DRILLING OF T	perti- to 17½" set 1.32,	
Spudded 26" hole 8:4 surface with redi-mand hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of Guide shoe so seal(yield of and float of 18 hrs. Nurilling.	TECHNOLOGIAN	
Spudded 26" hole 8:4 surface with redi-mm hole 3:00 AM 12-11-1851', insert float awt 14.8). PD 12:15 held okay. Circulat and tested to 500 ps	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril si for 30 minutes, OK. Res	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of the drilling of the seal (yield of the last of	perti- to 17½" set 1.32,	
Spudded 26" hole 8:4 surface with redi-mm hole 3:00 AM 12-11-1851', insert float awt 14.8). PD 12:15 held okay. Circulat and tested to 500 ps	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril si for 30 minutes, OK. Resolution of the contract of	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas led out 7:15 AM 12-duced hole to 11".	conductor at NM. Resumd set 851'. 4#/sx Cello pressure 13-90. Woo Resumed di	nd cemented to ded drilling of Guide shoe so seal (yield of and float of 18 hrs. Nurilling.	perti- to 17½" set 1.32,	
Spudded 26" hole 8: surface with redi-mi hole 3:00 AM 12-11-1851', insert float swt 14.8). PD 12:15 held okay. Circulat and tested to 500 ps	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril si for 30 minutes, OK. Resolute 1 Color of the	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas	conductor as NM. Resum set 851'. 4#/sx Cello	nd cemented to ded drilling of the drilling of the seal (yield of the last of	perti- to 17½" set 1.32,	
Spudded 26" hole 8: surface with redi-mi hole 3:00 AM 12-11-1851', insert float with 14.8). PD 12:15 held okay. Circulate and tested to 500 ps	40 AM 12-7-90 with rathole ix. Notified Dale Carpent 90. Ran 20 joints 13-3/8" set 808'. Cemented w/900 PM 12-12-90. Bumped plug ted 240 sacks. WOC. Dril si for 30 minutes, OK. Resolute 1 Color of the	. Set 40' of 20" of er, BLM, Carlsbad, 54.5# J-55 casing sx "C", 2% CaCl, 1/ to 600 psi, releas led out 7:15 AM 12-duced hole to 11".	conductor at NM. Resumd set 851'. 4#/sx Cello pressure 13-90. Woo Resumed di	nd cemented to ded drilling of Guide shoe so seal (yield of and float of 18 hrs. Nurilling.	perti- to 17½" set 1.32,	