

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

NOV 1 1991

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Hanagan Petroleum Corporation

O. C. D.  
ARIESA OFFICE

3. Address and Telephone No.

P.O. Box 1737 - Roswell, NM 88202

505-623-5053

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 990' FEL Sec. 1, T22S, R31E

5. Lease Designation and Serial No.

NM-43556

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Unocal - HPC Federal #2

9. API Well No.

30-015-26849

10. Field and Pool, or Exploratory Area

Livingston Ridge Del.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Intermediate  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/18/91 - TD 11" hole @ 4254' - Ran 136 jts. new 32# J-55 8 5/8" casing, shoe @ 4253' & float collar @ 4211' - cemented w/1200 sx. Halliburton-Lite w/1/4# Flocele & 10# salt per sx., tailed in w/250 sx. Class "C" w/2% CaCl, plug down @ 3:30 A.M., circ. 130 sx. to pit. Test casing to 1000 psi. Nippled up BOP & pressure tested to 3000# w/Safety Test. Drilled out @ 10:30 P.M. 10/18/91, drilling in 7 7/8" hole.

14. I hereby certify that the foregoing is true and correct

Signed

Title Asst. Vice President

Date 10/23/91

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side