

+ dsf
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED
APR 27 1992

O. C. D.

WELL API NO. 30-015-26973
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2597
7. Lease Name or Unit Agreement Name Flora AKF State
8. Well No. 1
9. Pool name or Wildcat Undes. Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3526' GR

4. Well Location Unit Letter <u>N</u> : <u>660</u> Feet From The <u>South</u> Line and <u>2310</u> Feet From The <u>West</u> Line
Section <u>2</u> Township <u>22S</u> Range <u>31E</u> NMPM <u>Eddy</u> County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 7:45 PM 3-31-92. Set 40' of 20" conductor and cemented to surface. Notified NMOC, Artesia, NM of spud. Resumed drilling 17-1/2" hole 3:30 PM 4-17-92. Ran 20 joints 13-3/8" 54.5# J-55 casing set 861'. Guide shoe set 861', insert float set 818'. Cemented w/ 600 sx "HLC" + 2% CaCl2 + 1/2#/sx Flocele (yield 1.89, wt 12.9). Tailed in w/200 sx "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 11:05 PM 4-18-92. Bumped plug to 400 psi, float held OK. Circulated 190 sacks to pit. WOC. Weld on head. NU BOP. WOC. Tested hydril and pipe rams to 500 psi. WOC.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-21-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY _____ TITLE _____ DATE SEP 5 1994

CONDITIONS OF APPROVAL, IF ANY: