

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OFFICE FOR NUMBER  
OF COPIES REQUIRED  
(Other instructions on re-  
verse side)

Modified Form No.  
NM060-3160-4  
LEASE DESIGNATION AND SERIAL NO.  
NM-19246

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. NAME OF OPERATOR  
Strata Production Company  
3. ADDRESS OF OPERATOR  
P. O. Box 1030, Roswell, New Mexico 88202-1030  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirement.  
See also space 17 below.)  
At surface

3a. Area Code & Phone No.  
505-622-1127

1750' FNL & 1850' FEL

O. C. D.

14. PERMIT NO.  
30-015-26992  
15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
2998' GL

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
Nash Unit  
8. FARM OR LEASE NAME  
Nash Draw  
9. WELL NO.  
#10  
10. FIELD AND POOL, OR WILDCAT  
Nash Draw Delaware  
11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA  
Section 13-23S-29E  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF  
FRACTURE TREAT  
SHOOT OR ACIDIZE  
REPAIR WELL  
(Other)

PULL OR ALTER CASING  
MULTIPLE COMPLETE  
ABANDON\*  
CHANGE PLANE

WATER SHUT-OFF  
FRACTURE TREATMENT  
SHOOTING OR ACIDIZING  
(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL  
ALTERING CASING  
ABANDONMENT\*

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/12/92

Drilled to 3015'. Ran 45 joints 8 5/8" 24# J55 casing and 27 joints 8 5/8" 32# J55 casing. Cemented at 3015' with 1050 sacks Halliburton Lite with 10# salt and 1/4# Kwikseal per sack. Tail in with 200 sacks Premium Plus with 5# salt per sack. Circulated 180 sacks cement to pit. Plug down at 12:15 PM on 12/12/92. WOC. Pressure test BOP and casing to 500#. Held OK.



18. I hereby certify that the foregoing is true and correct

SIGNED

Carol J. Garcia

TITLE Production Supervisor

DATE 12/14/92

(This space for use by the Bureau of Land Management)

APPROVED BY

APPROVAL IF ANY  
JAN 4 1993

TITLE

DATE

CARLSBAD, NEW MEXICO

See Instructions on Reverse Side