

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Cons.
N.M. Div-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993

clsf

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Nearburg Producing Company

3. Address and Telephone No.
3300 North "A" Street, Bldg 2, Ste 120, Midland, TX 79705 (915) 686-8235

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit F, 2007' FNL and 1470' FWL, Section 32-24S-29E

5. Lease Designation and Serial No.
NM 54289

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Emerald 32 Federal #1

9. API Well No.
30-015-26996

10. Field and Pool, or Exploratory Area
Undesignated Delaware

11. County or Parish, State
Eddy County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Nearburg Producing Company requests for Plug and Abandon on the above referenced well.

- 1) Tag bottom to 4695'.
2) Set 100' cement plug f/ 4150' to 4250'.
3) Cut csg @ 3000' & pull.
4) Set 100' plug 50' in and 50' out stub. Tag.
5) Set 100' plug f/ 2500' to 2600'. to 2700' TAG. 6) SET 100' PLUG F/1200-1300'.
7) Set 100' plug f/ 554' to 654'. (Base 8-5/8" 604')
8) Set 40' surface plug.
9) Install dry hole marker.

NOTE: Well was TA'd back on 8/19/98. Subsequent Report filed on 09/01/98 - never approved. MIT test run on 8/22/01. Subsequent report filed on 02/04/02. Approved by Joe Lara for 90 day extension to expires 05/07/2002.

NOTE: ISOLATE SALT SECTION AS SHOWN.

14. I hereby certify that the foregoing is true and correct

Signed *Kim Stewart*
(This space for Federal or State office use)

Title Regulatory Analyst

Date 02/08/2002

Approved by
Conditions of approval, if any:

(ORIG. SGD.) ALEXIS C. SWOBODA

Title

PETROLEUM ENGINEER

Date

FEB 12 2002

Title 1E
statement

Accepted for record

only

FEB 13 2002

and willfully to make to any department or agency of the United States any false, fictitious or fraudulent

See Instruction on Reverse Side

RECEIVED
2002 FEB 11 AM 10:17
BUREAU OF LAND MGMT
ROSWELL OFFICE