Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

WELL API NO.

•	P.O. Box 2088 RECEIVED		30-015-27017		
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico 87504-2088 MAR 0 2 1993		5. Indicate Type of	of Lease	FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410		O. C. D.	6. State Oil & Ga V-3589	<del></del>	FEE
SUNDRY NOTICES ( DO NOT USE THIS FORM FOR PROPOS DIFFERENT RESERVOIF (FORM C-101)	7. Lease Name or Unit Agreement Name				
i. Type of Well: OIL GAS WELL WELL WELL	OTHER		Pauline ALB State		
<ol> <li>Name of Operator         YATES PETROLEUM CORPORATI</li> </ol>	on 🗸		8. Weii No. 2		
. Address of Operator			9. Pool name or Wildcat		
105 South 4th St., Artesi	a, NM 88210		West Sand	Dunes Delaware	2
	Feet From The South  Township 23S Ra  10. Elevation (Show whether		Feet From	n The East Eddy	Line
	3381' GR		· .	<u> </u>	
11. Check App	ropriate Box to Indicate l	Nature of Notice, Ro	eport, or Othe	r Data	
NOTICE OF INTEN	SEQUENT REPORT OF:				
ERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING	
EMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING	OPNS.	PLUG AND ABANDO	MENT
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB XX			
OTHER:		OTHER:	<del></del>	·	🗆
12. Describe Proposed or Completed Operations work) SEE RULE 1103.	Clearly state all pertinent details, ar	nd give pertinent dates, inclu	ling estimated date o	of starting any proposed	
Ran 194 joints of 5-1/2" 5-1/2" 17# J-55 (1172.58' of 5-1/2" 17# J-55 (592.6 set at 8031'. DV tool set 175 sacks "H", 8#/sack CS 1.75, weight 13.6). Tail salt (yield 1.38, weight	), 152 joints of 5-63') set at 8070'. Et at 6606'. Cement E, 5#/sack gilsonit ed in with 65 sacks	1/2" 15.5# J-55 Float shoe set and in two stages e, .6% CF-14 and "H", 10% Thixad	(6315.62') at 8070'. s as follow d .35% Thri d, 8#/sack	and 14 joints Float collar s: Stage 1: ftylite (yield Hiseal and 10%	

through DV tool for 3-1/2 hours. Stage 2: 450 sacks Pacesetter Lite "C", 5#/sack gilsonite, .4% CF-14 and 5#/sack salt.(yield 1.85, weight 12.7). Tailed in with 150 sacks "H", 8#/sack CSE, 5#/sack gilsonite, .6% CF-14 and .35% Thriftylite (yield 1.75, weight 13.6). PD 3:20 AM 2-15-93. Bumped plug to 2650 psi, OK.

(This space for State Use) ORIGINAL SIGNED BY				
TYPEOR PRINT NAME Juanita Goodlett			TELEPHONE NO.	505/748-1471
SIGNATURE Kusty Klein	тпле	Production Clerk	DATE Feb.	26, 1993
I hereby certify that the information above is true and complete to the best of my know	viedge and belief.			

MIKE WILLIAMS

SUPERVISOR, DISTRICT IF

MAR 1 9 1993 - DATE

APPROVED BY-