

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator Maralo Inc.		Lease Little Bear State Ut.		Well # 1	
Location of Well	Unit J	Section 18	Township 24	Range 25	County Eddy
Drilling Contractor WEEK #3			Type of Equipment		

APPROVED CASING PROGRAM

* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	54.5#		550'	500 Surf.
11	* 8 5/8	32# K-55		3000	1500 Circ
7 7/8	5 1/2	15.5#		5600'	1000 Circ to

Casing Data: 8 5/8

Surface joints of 13 3/8" inch 54.5 # Grade K-55

(Approved) (Rejected)

Inspected by N.S. date July 30, 92

Cementing Program

Size of hole 17 1/2" Size of Casing 13 3/8" Sacks cement requiredType of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 579' Set 579' Feet of 13 3/8" Inch 54.5 # Grade K-55(New) used csg. @ 579' with 650 2%cc sacks neat cement around shoe+ sax additives Plug down @ 4:00 (AM) (PM) Date Aug. 4, 92Cement circulated yes No. of Sacks 150 sxCemented by Dowell Witnessed by Mike StubblefieldTemp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date Method Used Witnessed by Checked for shut off @ (AM) (PM) Date Method used Witnessed by Remarks:

Wtr in hole 35'-65'