## NM OIL CONS. COMMISSION DRAWER DD ARTESIA. NM 88210



Form 3160-5

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED (June 1990) Budget Bureau No. 1004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-40655 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well CONFIDENTIAL Oil Gas Well Well 8. Well Name and No. 2. Name of Operator Amax 24 Federal No. 7 Pogo Producing Company 9. API Well No. 3. Address and Telephone No. 30-015-27129 P. O. Box 10340, Midland, TX 79702 (915)682-6822 10. Field and Pool, or Exploratory Area AHG () 8 1996 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sand Dunes Brushy Canyon 11. County or Parish, State OIL CON. DIV. Eddy County, NM 1980' FNL & 330' FWL, Sec. 24, T23S, R31E CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction XX Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud & Set Surface Csg Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* MIRU Nabors Rig #301. Spud well @ 1045 hrs CDT 8/1/93. Drilled 17 1/2" hole to 825'. TD reached @ 0730 hrs CDT 8/2/93. Ran 19 jts - 13 3/8", 54.5#, J-55, ST&C casing. TDGS @ 825'. IFV @ 783'. Howco cemented casing with 750 sx Halliburton Lite @ 12.7 ppg followed by 200 sx Premium Plus @ 14.8 ppg. Plug down @ 1215 hrs CDT 8/2/93. Recovered 175 sx excess cement. WOC 24 hrs. Make cut-off. Weld on casing head. NU BOP's and test to 1000 psi. ACCEPTED FOR RE 73 [11] 14. I hereby certify that the foregoing is true and correct Title Division Operations Manager (This space for Federal or State office use Approved by Conditions of approval, if any: