

clsF

RECEIVED

JUN - 6 '94

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P.O. Box 10340, Midland, Texas 79702-7340 (915) 682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 330' FWL, Section 28, T-23-S, R-31-E

5. Lease Designation and Serial No.

Office NM-40659

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pure Gold "D" No. 3

9. API Well No.

30-015-27139

10. Field and Pool, or Exploratory Area

Sand Dunes W., Delaware

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Intermediate Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole 800'-4025'. T.D. Reached 13:00 hrs CST, 11/26/92. Ran 8-5/8", 24# & 32#, J-55, ST&C casing. Guide Shoe @ 4025'. Float collar @ 3979'. Howco cemented with 1300 sx Halliburton Lite @ 12.4 ppg. Followed by 200 sx Premium @ 14.8 ppg. Plug down with 1420 psi @ 02:00 hrs., CST 11/27/92. Circ'd 200 sx excess cement. NU BOP's, test casing and BOP's to 1500 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title Division Operations Manager

Date Dec. 14, 1992

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations.

\*See instruction on Reverse Side