Multi-Point Surface Use and Operations Plan Pure Gold C-17 No.4

Page 2

- 6. SOURCES OF CONSTRUCTION MATERIALS.
 - A. Any caliche required for construction of the drilling pad will be obtained from a pit located of the wellsite.
- 7. METHODS OF HANDLING WASTE DISPOSAL
 - A. Drill cuttings will be disposed of in the reserve pits.
 - B. Drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry.
 - C. Water produced during operations will be either placed in the reserve pits and allowed to evaporate or collected in tanks until hauled to an approved disposal system or a separate disposal application will be submitted to the BLM for appropriate approval.
 - D. Oil produced during operations will be stored in tanks until sold.
 - E. Human waste will be buried.
 - F. Trash, waste paper, garbage, and junk will be collected in trash trailers and disposed of in an approved waste facility such as a land fill. The trash trailers contain all of the material to prevent scattering by the wind.
 - G. All trash and debris will be buried or removed from the wellsite within 30 days after finishing drilling and/or completion operations. Somial is not permitted on site.
- 8. ANCILLARY FACILITIES.

None required

9. WELLSITE LAYOUT

- A. Exhibit G shows the dimensions of the well pad and reserve pits, and the location of major rig components.
- B. The ground surface of the location is located among several sand dunes with vegetation growing on them. The location will constructed by leveling the necessary dune and covering the sand with at least six inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. A 400' X 400' work area which will contain the pad and pit area has been staked and flagged.
- 10. PLAN FOR RESTORATION OF THE SURFACE.
 - A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.