

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

FEB 24 1993

O. C. D.

WELL API NO. 30-015-27205
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Gumby
8. Well No. 1
9. Pool name or Wildcat Und Delaware

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER	
2. Name of Operator Chi Operating Inc. ✓	
3. Address of Operator P. O. Box 1799, Midland, TX 79702	
4. Well Location Unit Letter <u>I</u> : <u>990</u> Feet From The <u>East</u> Line and <u>2310</u> Feet From The <u>South</u> Line Section <u>23</u> Township <u>24-S</u> Range <u>28 -E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 2933 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spud @ 2:30 am on 11/26/92.
- Ran 13 3/8" 54.5# csg set @ 246' cmt w/ 400 sk Class C. Did not circ. Circ w/ 400 sks down backside - Test to 1,000 PSI for 1 hr. WOC 18 Hrs.
- Ran 22 jts of 8 5/8 24# csg set @ 595' cmt w/ 600 sk Class C. Circ 50 sk to pit. Test to 1,000 PSI for 1 hour. WOC 18 Hrs.
- Ran 149 jts 5 1/2 15.50# csg set @ 6250'. Cmt w/ 260 sks Class C. ***

CEMENT ADDITIVES:

* 400 SKS w/ 2% CaCl₂

** 600 SKS w/ 2% CaCl₂

*** 260 SKS w/ 40% FL; 1% BOND. AGT; 2/10% F.W. CONT.; 2/10% DEFAMER

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David H. Harrison TITLE President DATE 2/15/93

TYPE OR PRINT NAME David H. Harrison - REFILED BY MIKE FEAGAN 7/30/93 TELEPHONE NO. (915) 685-500

(This space for State Use)

APPROVED BY Ronald TITLE Secretary DATE 2/15/93

CONDITIONS OF APPROVAL, IF ANY: