Form 3160-5

June 1990)

MY OIL COMS, WATER Brawer DD Artesia IN HERIO

FORM APPROVED Budget Bureau No. i004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No.

UNITED STATES

DEPARTMENT OF THE INTERIOR

	The second of th
	this form for proposals to drill or to deepen or reentry to a different reservoir.
D	the form for proposals to drill or to deepen of feently to a gittle entities of the
Do not use	(M2stotti tot bioboggia to gitti of ta gappari a service was serviced
	The same area area area area area area area a
	THE WARDING ATION FOR REPMILE TOT SHOUDING

July BUREAU OF LAND	5. Lease Designation and Serial No. NM-45235		
SUNDRY NOTICES AND	REPORTS ON WELLS to deepen or reentry to a different reservoir. RMIT—" for such proposals	6. If Indian, Ailottee or Tribe Name	
SUBMIT IN T	IIIM 2 1 1000	7. If Unit or CA. Agreement Designation	
Santa Fe Energy Operation Santa Fe Energy Operation Santa Fe Energy Operation Santa Fe Energy Operation Address and Telephone No. 550 W. Texas, Suite 1330, Midla Location of Well (Footage, Sec., T., R., M., or Survey Description (J), 1880' FSL and 1980' FEL, Sec. CHECK APPROPRIATE BOX(s) TO	and, TX 79701 (915) 687-3551	8. Well Name and No. Pure Gold C-17 Fed #8 9. API Well No. 30-015-27420 10. Field and Pool. or Exploratory Area Sand Dunes, W. (Delaware) 11. County or Parish. State Eddy Co., NM	
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other Ran casing string	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13. Describe Proposed or Completed Operations (Clearly state all pertugive subsurface locations and measured and true vertical detections). 5/26/93: Depth 4070 . RU and n	can 94 jts 8-5/8" 32# K-55 LT&C ca		

Cemented w/ 1450 sx "C" Lite + 9 pps salt and 1/4 pps Celloflake. Tail with 500 sx C1 "C" + 2% CaCl2. Plug down at 7:00 a.m. Circ 125 sx to pit. WOC. Cut off csg and weld on head.

5/27/93: NU and test BOPs, choke and all valves to 2000 psi. Hydril to 1500 psi - ok. PU DC's and TIH. WOC total of 24 hours. Test casing to 1500 psi - ok. Resume drilling operations.

Havid Rollass.

Thereby certify that the foregoing is true and correct	TideSr	. Production Clerk	Date	May 28, 1993
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title		Date	·