

AUXILIARY EQUIPMENT

DRAWWORKS	BDW 650M 650 HP, with Parmac Hydromatic brake
ENGINES	Two Caterpillar D-353 diesels rated at 425 HP each
ROTARY	Ideco 23", 300 ton capacity
MAST/SUB	Ideal 132', 550,000 lb rated static hook load with 10 line Wagner 15' high substructure
TRAVELLING EQUIPMENT	Gardner-Denver. 300 ton, 5 sheave w/ BJ 250 ton hook. Brewster Model 7 SX 300 ton swivel.
PUMPS	Continental-EMSCO DC-700 and DB-550, 5 1/2 X 16" Duplex, Compound driven.
PIT SYSTEM	1-Shale Pit 6X7X35', 1-Settling Pit 6X7X38', 1-Suction Pit 6X7X34' w/ 5 mud agitators. Two centrifugal mud mixing pumps and a Double Screen Shale Shaker.
LIGHT PLANT	Two CAT 3306 diesel electric sets 180 KW prime power.
BOP EQUIP	13 5/8" 5000 psi WP double ram and 13 5/8" 5000 psi WP Shaffer Annular Preventer. Choke manifold rated at 5000 psi. Valvcon 5-station 80 gallon closing unit.

Exhibit D
Santa Fe Energy Operating Partners, L.P.
North Pure Gold 9 Federal No. 9
Section 9, T-23S, R-31E
Eddy County, New Mexico