

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

AUG 26 1993

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FNL & 1980' FEL, Sec. 35, T23S, R31E

5. Lease Designation and Serial No.

NM-19199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Calmon #20

9. API Well No.

30-015-27549

10. Field and Pool, or Exploratory Area

Ingle Wells Delaware

11. County or Parish, State

Eddy

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Intermediate Casing

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 11" hole 816' to 4303'. TD reached 0500 hrs CDT 7/22/93. Ran 103 jts 8 5/8", 24# & 32#, J-55, ST&C casing. Guide shoe @ 4303'. Float collar @ 4257'. Howco cemented casing with 1600 sx Halliburton Lite @ 12.4 ppg followed by 200 sx Premium Plus @ 14.8 ppg. Plug down @ 1545 hrs CDT 7/22/93. Recovered 200 sx excess cement. WOC 24 hrs. Make cut off. Weld on casing head. NU BOP's and test to 1500 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title Senior Operations Engineer

Date 8/25/93

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: