Form 3160-5 (June 1990)

UNITY STATES DEPARTMEN. OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Artesia,	NM	90510	
FORM	л APF	ROVED	
Davidson Da		- 4004 0435	

Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NM 0533177-A Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ⊠ Oil Well ☐ Gas Well Other 8. Well Name and No. 2. Name of Operator **DÉVON ENERGY CORPORATION (NEVADA)** Todd "24G" Federal #7 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-27692 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Ingle Wells (Delaware) Sec G-24-T23S-R31E 2310' FEL & 1650' FNL 11. County or Parish, State Eddy Cnty, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Phans Recompletion **New Construction** Plugging Back Subsequent Report Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud and running csaing strings Dispose Water (Note: Report results of m Completion or Recompletion Report and Log form 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled five subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* SPUD on 05-26-95. Drilled 17 1/2" hole to 858'. On 05-28-95 ran 19 its 13 3/8" 48# H-80 ST&C csg. set at 858'. Cemented with 500 sx Pacesetter Lite + 200 sx Class C. Circ'd cement to surface. Drilled 11" hole to 4360'. On 06-04-95 ran 99 its 8 5/8" 24# J-55 ST&C csg, set at 4359'. Cemented with 1300 sx Pacesetter Lite + 200 sx Class C. Circ'd cement to surface. Drilled 7 7/8" hole. Reached TD 8650' on 06-16-95. Schlumberger ran LDT-CN Colemb at 1/4/45 [59] On 06-18-95 ran 201 jts 5 1/2" 17# and 15.5# J-55 LT&C csg, set at 8650'. Cemented 1st stage with 600 sx Class H. Circ'd cement to surface. Opened DV tool. Cemented 2nd stage with Pacesetter Lite + 335 sx Class C. Circ'd cement to surface. OIL CON. DIV. DIST. 2 Released rig on 06-19-95. Waiting on completion. 14. I hereby certify that the foregoing is true and correct Gerald T. Pepper Date 7/27/95 Title District Engineer (This space for Federal or State office use) ACCEPTED FOR RECORD Approved by Title Conditions of approval, if any: