

clsp

Form J160-5
 (June 1990)

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
 Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Kaiser-Francis Oil Company

3. Address and Telephone No.

P. O. Box 21468, Tulsa, OK 74121-1468

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface: 10' FSL & 1960' FEL of Sec. 17-23S-31E

BHL: 667' FNL & 1800' FEL of Sec. 20-23S-31E

FORM APPROVED
 Budget Bureau No. 1004-0135
 Expires: March 31, 1993

5. Lease Designation and Serial No.

NM - 38463

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pure Gold B Federal #9

9. API Well No.

30-015-27841

10. Field and Pool, or Exploratory Area

W. Sand Dunes (Delaware)

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Ran Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Casing and Cementing Detail

Ran 13 3/8", 48#, H-40 casing and set @ 700'. Cemented with 700 sxs 'C'. Circ'd to surface. Tested to 600# - held okay.

Ran 8 5/8", 24# & 32#, J-55 casing and set @ 4020'. Cemented w/1200 sxs 'C' Lite + 200 sxs C1 'C'. Circ'd to surface. Tested to 1000# - held okay.

Ran 5 1/2", 17#, J-55 casing and set @ 8120'. Cemented first stage w/600 sxs 'H'. Set DV tool @ 6163' and cemented second stage w/1200 sxs 'C' Lite + 100 sxs 'C' Neat. TOC @ 1600'. Tested to 1000# - held okay.

Please note that this sundry notice replaces sundry notice dated 7/19/94 in which we detailed the cementing of the conductor and surface strings but inadvertently filed it as well #1.

14. I hereby certify that the foregoing is true and correct

Signed

Charlotte Van Valkenburg

Charlotte Van Valkenburg

Technical Coordinator

Date 9/9/94

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

J. L. L...

1994