

PAGE START DATE: 10/ 2/9  
 PAGE START TIME: 4:57: 0  
 DATA FILE: 7

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	500.00	77.25	
0.800	3020.00	85.00	BREAK
0.817	3084.00	88.50	
0.867	3286.00	87.00	
0.933	3546.00	89.25	
0.983	3700.00	89.00	
1.067	3983.00	92.25	
1.117	4160.00	91.50	
1.150	4288.00	94.25	
1.183	4420.00	93.50	
1.217	4554.00	95.25	
1.233	4624.00	94.50	
1.250	4696.00	96.00	
1.292	4873.00	112.75	
1.308	4949.00	111.50	
1.317	4987.00	113.25	
1.333	5066.00	111.25	
1.350	5143.00	112.50	
1.358	5181.00	111.25	
1.367	5219.00	116.00	
1.383	5298.00	115.25	
1.400	5383.00	121.75	
1.408	5427.00	116.75	
1.417	5471.00	120.50	
1.433	5561.00	116.75	
1.450	5646.00	121.00	
1.483	5822.00	116.00	
1.500	5875.00	122.50	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

OCTOBER 1, 1996 @ 2:25 PM

DATE AND TIME SURVEY MADE:

OCTOBER 2, 1996 @ 5:45 AM

AMOUNT AND TYPE CEMENT USED:

915 SACKS 50:50 POSMIX, 2.8# KCL,  
 3/10% HALAD 322 RUN THROUGH D.V.  
 TOOL AT 5898' BEHIND 5½" CASING  
 IN A 7-7/8" HOLE.

DEPTH FIGURED FROM:

GROUND LEVEL