12.

TYPE OF SUBMISSION

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N. U	≘ns	visio	
. S. 3 s t		•	

tesia, N

TYPE OF ACTION

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

2834 FORM APPROVED Budget Bureau No. 1004-0135 5. 1

6. If Indian, Allottee or Tribe Name

		Expires:	M	arch	31, 199	3	
5.	Lease	Designati	ion	and	Serial	No.	
N	M-0	41769	96				

Use "APPLICATION FOR PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas Well Other	8. Well Name and No.
2. Name of Operator Pogo Producing Company AUG 3 3 1397	Lost Tank 4 Federal #5 9. API Well No.
3. Address and Telephone No. P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822	30-015-29732 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Lost Tank Delaware West 11. County or Parish, State
1650' FNL & 2310' FWL, Section 4, T22S, R31E	Eddy County, NM
2. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA

Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud & Set Surface Csg	Dispose Water
		(Note: Report results of multiple completion on Well
12 Decit Decides Complete Comp	I pertinent details, and give pertinent dates, including estimated date of starting an	Completion or Recompletion Report and Log form.)
13. Describe Proposed of Completed Operations (Clearly state at	i pertinent details, and give pertinent dates, including estimated date of starting an	y proposed work. If well is directionally diffied,

Spud & Set Surface Csg - MIRU TMBR/Sharp #10. Spud @ 2215 hrs CDT 8/14/97. Drld 14-3/4" hole to 656'. TD reached 1345 hrs CDT 8/15/97. Ran 14 jts 10-3/4" 40.5# J-55 ST&C csg. TPGS @ 656'. IFV @ 607'. Howco cmt'd csg w/ 350 sxs Halliburton Lite + 2% CaCl₂ @ 12.7 ppg followed by 200 sxs Cl "C" + 2% CaCl2 @ 14.8 ppg. Plug down @ 1900 hrs CDT 8/15/97. Recov 125 sxs excess cmt. WOC 24 hrs. Make cut-off. Weld on casing head. NU BOP's & test to 500 psi.



14. I hereby certify that the foregoing is true and correct		
Signed Daniel Smo	Title Senior Operations Engineer	Date 8/19/97
(This space for Federal or State office use)		
Approved by Conditions of approval, if any:	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*