

45P

RECEIVED BY

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

JAN 30 1985 SUNDAY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. O. C. D.

ARTESIA OFFICE

OTHER RE-ENTRY

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660 FNL & 760 FWL, Sec. 21-26S-27E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3235' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 38459

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Welch "ABV" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat - Bone Springs

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit D, Sec. 21-T26S-R27E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Re-Entry, began drilling out

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

- 1-20-85. RUPU. Drill 20' surface plug. Found hole in casing at 530'.
1-21-85. Washed and drilled to 3940'. Cemented w/220 sx Class C 3% CaCl2.
Circulated from hole in 9-5/8" casing at 530' via 13-3/8" to surface.
PD 6:00 PM 1-21-85. Shut in 4 hrs.
1-22-23-85. Washed and drilled cement to 8000'±.

18. I hereby certify that the foregoing is true and correct

SIGNATURE *Quanta D. Smith*

TITLE Production Supervisor

DATE 1-25-85

(This space for Federal or State office use)

APPROVED BY *ACCENTED FOR RECORD*
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 28 1985

*See Instructions on Reverse Side