(November Const. By By Comery Services	EPARTMENT OF THE INTE	SUBMIT IN TRII ATE (Other instruction in re	
444 0	BUREAU OF LAND MANAGEM		NM 38459
JUL 24 1985 SUNDR	Y NOTICES AND REPORTS of for proposals to drill or to deepen or plessed a drill or to deepen or plessed a drill or to deepen or plessed and the dr	S ON WELLS	8. IF INDIAN, ALLOTTEE OR TRIBE NAME
I. ARTESIA, OFFICE			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME		
Yates Petroleum Corporation			Welch "ABV" Federal
3. ADDRESS OF OPERATOR			9. WELL NO.
207 South 4th S	1		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 			10. FIELD AND POOL, OR WILDCAT Wildcat
660 FNL	11. SEC., T., B., M., OR BLK. AND SURVEY OR AREA		
			Unit D, Sec. 21-T26S-R27E
14. PERMIT NO. 15. BLEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH 13. STATE
	3235' GR		Eddy NM
16.	Check Appropriate Box To Indicate	e Nature of Notice, Report, or (Other Data
	CE OF INTENTION TO:		UENT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING		
FRACTURE TREAT	MULTIPLE COMPLETE	WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING WELL ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	1	X ALTERING CASING X ABANDONMENT®
REPAIR WELL	CHANGE PLANS	(Other) Repair well	
(Other)		(NOTE: Report results	s of multiple completion on Well
17. DESCRIBE PROPOSED OR COM	PLETED OPERATIONS (Clearly state all perti	neut details and give postinent detag	oletion Report and Log form.) , including estimated date of starting any cal depths for all markers and zones perti-
6-20-85 - 6-28-85. plug 830'. Waited casing at 530'. S 9-5/8" casing to 5 6-29-85. Ran 120 7-2-85. Ran casin tool. TIH w/mill Tested 7" casing t 7-8-85. Acidized w/2000 gals 7½% Sp 7-17-85. Frac'd (RU unit. Pumped 100' of 3 hrs. Tagged plug. Pum I overnight. Had 0 psi if 70'. Washed and drilled jts 7" set 5000'. Bottom is alignment tool to 4988' tooth bit. Drilled out at 2000 psi for 30 minutes perfs 5820-22' (4 holes) pearhead acid and ball sea (via 2-7/8" tubing) perfor 50000# (60000# 12/20 + 2000)	cement plug of 35 sx C1 nped 250 sx C1 C w/2% Can AM. Squeezed w/250 to 5000'. In and top joint 32# and '. Cemented w/125 sx Calignment tool at 5000's, OK. Cleaned out to 5 , 5826-30' (8 holes) and alers. rations 5820-40' (16 ho	C w/2% CaCl2. Top of aCl2 in hole in 9-5/8" sx to 2000 psi. Drilled middle joints 23#. 1 C. TOOH w/setting . Cleaned out to 5300'. 870'. d 5838-40' (4 holes)
18. I hereby certify that the f	7)		
sideriani	ta Sodell TITLE Pr	oduction Supervisor	DATE
(This space for Federal or	: State office use)		

APPROVED BY ACCEPTED FOR RECORD TITLE CONDITIONS OF APPROVAL, IF ANY: DATE .

JUL 23 1985

*See Instructions on Reverse Side