Form 3160-5 (June 1990)

Approved by Conditions of approval, if any

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. DIV-DIST. ZBudget Bureau No. 1004-0135 1301 W. Grand Avenue Expires. March 31, 1993 Artesia, NM 88210 LC 064756

Date

SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals

7 If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1 Type of Well Gas Oil X well 8 Well Name and No Well Other RT Wilson Fed. #5 2 Name of Operator Aghom Operating, Inc. 9. API Well No. 3 Address and Telephone No. : 1 30-015-05868 P. O. Box 12663 Odessa, TX 79768 (915) 550-0804 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Mason Delaware, North 1980 FSL, 1980 FEL, Sec. 24, T 26S, R 31E, Unit J 11 County or Parish, State Eddy County, NM 12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION X Abandonment Notice of Intent Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off X Final Abandonment Notice Altering Casing Conversion to Injection Other Dispose Water Note: Report results of multiple completion on West Completion or Recompletion Report and Log ferm: 13 Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)* Notify BLM 24 hrs. before starting 1.12/31/01 Set CIBP @ 4200, dumped 35 ft. cmt. on top. Circ. hole w/ mud laden fluid. 2.12/31/01 Perf 4 1/2 csg. @ 1040. WIH w. 4 1/2 pkr. Sqz 50 sx. class "C" neat cmt. Disp. to 940 ft. 3.01/02/02 Tagged plug @ 877 ft. 4.01/02/02 Perf. 4 1/2 csg. @ 50 ft. Pumped 50 sx. class "C" neat cmt. down 4 1/2 and up 8 5/8 csg. to surface. WOC 2 hrs. install Dry hole Marker. Approved as to place for a Lizabity under broad to an surtees restoration is confide SBABYAK 14. Thereby certify that the foregoing is true and correct 10. B. Title cement supervisor 01/05/02 Date (This space for Federal of State office use

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title