

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	/
FILE	/-
U.S.G.S.	
LAND OFFICE	
OPERATOR	3

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

O. O. L.  
ARTESIAN OFFICE

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
State - K-4562

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name Cotton Draw Unit
2. Name of Operator TEXACO Inc. ✓	8. Farm or Lease Name Cotton Draw Unit
3. Address of Operator P. O. Box 728 - Hobbs, New Mexico	9. Well No. 65
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>25-S</u> RANGE <u>31-E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 3475' (D. F.)	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to change plans and set the following plugs & Perforate:

1. Set a 60 Sx. Cement Plug from 18,800' to 18,630', (Ellenburger)
2. Set a 60 Sx. Cement Plug from 17,220' to 17,070', (Fusselman)
3. Set an unknown number of Sx. from 16,780' to 16,200' in stages until the top of plug is at 16,200' or above. The 8 5/8" O. D. casing is cemented at 16,250'.
4. Set a Cast Iron Bridge Plug at 15,050'.
5. Perforate the Casing with selected intervals from 14,867' to 14,787'. (Morrow Pool).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan Gillett TITLE Assistant District Supt. DATE May 18, 1967

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE MAY 19 1967

CONDITIONS OF APPROVAL, IF ANY: