

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.
NH 050200-A

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR SINCLAIR OIL CORPORATION		8. FARM OR LEASE NAME Guadalupe Ridge Unit	
3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico 38240		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' from the West line and 660' from the North line.		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR ELK. AND SURVEY OR AREA 22-T26S-R21E	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, OR, etc.)	12. COUNTY OR PARISH Eddy	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Run & cement 8-5/8" CD Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 11-1-68 Ran electric logs. Ran 8-5/8" CD 24# J-55 3R R-2 Csg set @ 2102' and cemented to w/375 sks. (300 sks. Class A 1% gel, 10# Gilsomite & 1/4# Flocale per. sk.
- 11-2-68 Slurry Wt. 13.8# plus 75 sks. Encor Neat (15# Slurry Wt.) Temperature survey indicated top of cement behind 8-5/8" CD csg @ 960'. WOC 24 hrs.
- 11-3-68 Ran D.P. to top cement @ 2070', test BCP and 8-5/8" CD casing to 2000' for 30" tested O.K. Drilled float & cement to 2102' and pressure tested 8-5/8" CD casing to 2000' for 30". Tested O.K. Drilling ahead.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Superintendent

DATE 11-1-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Orig&4cc: USGS, Artesia

cc: Mrs. M. M. Rhea, Santa Fe, N.M.

cc: Partners

cc: Regional Office

cc: File

*See Instructions on Reverse Side

APPROVED

R. L. BEECHER