

SUPPLEMENTAL DRILLING DATA

GP II ENERGY, INC.
Orig. American Quasar Petroleum Co.
WHITE CITY UNIT FEDERAL "1"
660 FSL & 1980 FEL (O)
Sec. 1, T25S, R25E
Eddy County, New Mexico

1. SURFACE FORMATION: Quaternary

2. ESTIMATED GEOLOGIC TOPS:

Base of Salt	1352
Delaware Sand	1611
Manzanita Marker	2626
Brushy Canyon	3320

3. ANTICIPATED HYDROCARBON BEARING ZONES:

Delaware Sand (oil)	3320
Cherry Canyon (oil)	3535

4. EXISTING CASING:

<u>CASING SIZE</u>	<u>FROM</u>	<u>TO</u>	<u>CEMENT</u>
20"	0'	30'	Circ.
13 5/8"	0'	328'	Circ.
9 5/8"	0'	1650'	750 sx.
7 5/8"	5020'	8500'	300 sx.

5. PROPOSED LINER AND CEMENTING PROGRAM:

<u>LINER SIZE</u>	<u>FROM</u>	<u>TO</u>	<u>CEMENT</u>	<u>GRADE</u>	<u>JOINT</u>
5 1/2"	1625'	3600'	400 sx.	k-55	LTC

A 5 1/2" production liner will be run to 3600' and hung off at approximately 1625'.

The 5 1/2" liner will be cemented with sufficient Light cement to cover the zones to be tested - approximately 300'.