

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY
SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved by
Budget Bureau No. 42-R1423.

5. LEASE DESIGNATION AND SERIAL NO.

NM-14778

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		RECEIVED		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR		JAN 21 1975		8. FARM OR LEASE NAME
Mobil Oil Corporation				
3. ADDRESS OF OPERATOR		O.C.C.		9. WELL NO.
Box 633, Midland, Texas 79701		ARTESIA, OFFICE		2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		1580' FSL & 1980' FWL of Sec. 22, T-25-S, R-29-E		10. FIELD AND POOL, OR WILDCAT
				Corral Draw (Morrow)
				11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA
				Sec. 22, T-25-S, R-29
14. PERMIT NO.	15. ELEVATIONS (Show whether SP, RT, CR, etc.)	3062 CR		12. COUNTY OR PARISH
				Eddy
				13. STATE
				New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Side Tract Hole xx

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1/16 2885 ND, 2446 drlg sidetracked 12 1/4 hole w/Dyna-Drill 1° @ 2416, drill from 2327-2416, POH, ran 10.1-48-5.0. HTC XV bit on Dyna-Drill 3° bent sub, 6 - 8" DC's & DP.

1/17 2885 ND, 2560 drlg anhy, 12 1/4 sidetracked hole, 10.0-50-28.0. 1° @ 2550, drld to 2560 w/Dyna-Drill, POH ran 12 1/4 hole opener & bottom hole reamer on 6 - 8" DC's & DP, reamed hole from 2300-2560, POH, prep to drill.

1/18 2885 ND, 2760 drlg anhy & salt, 12 1/4 sidetracked hole, 2° 2610; 2° 2653; 2° 2735. 9.7-46-4.0.

1/19 2921 drlg anhy & lm, 12 1/4 hole, 9.7-46-4.0. 2° @ 2802; 2° @ 2859.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Authorized Agent

DATE

1-21-75

(This space for Federal or State office use)

APPROVED

TITLE

DATE

COPIES OF THIS REPORT, IF ANY:

*See Instructions on Reverse Side