

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Kincheloe & Becker

JUN 21 1976

3. ADDRESS OF OPERATOR
859 Petroleum Building, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FSL, 660' FWL, Sec. 12, T-25S, R-26E
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3290.5 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 14124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12-25S-R26E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Complete Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-25-76 Ran 50-3/4"jts. 9.5# csg. @ 1998.6'. Cmted. w/ 175 sx. 50/50 pozmix, Class "C" w/ 2% gel and 8# salt per sx. Plug down 3:20 p.m., Tested to 600# held O.K.

5-29-76 Perforated 4 holes @ 1962' and 1966'. Reperforated 6 holes @ 1962' and 1966', pumped 250 gal. 15% HCL acid.

6-2-76 Reperforated 4 holes per ft. @ 1962-1970'. Treated 1500 gal. 15% acid. Swabbed dry, no show of oil or gas.

6-3-76 Set RTTS drillable bridge plug @ 1956' and squeezed all perforations w/ 100 sx. cmt.

6-4-76 Perforated 2 shots per ft. @ 1928-36' and 1942-48'. Treated w/ 1500 gal. 15% acid. Swabbed acid-water and trace oil.

6-9-76 Retreated perforations 1928-36' w/ 1000 gal. 15% HCL. Ran 2 3/8" tbg. and pump set @ 1950'. Testing on pump.

RECEIVED
JUN 11 1976

U. S. GEOLOGICAL SURVEY
ARTEZIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Dalton Kincheloe

TITLE

Operator

DATE

6/10/76

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

JUN 8 1976

*See Instructions on Reverse Side