Form 9-331 Dec. 1973

	Form Approved.				
٠.	Budget	Bureau	No.	42-R1424	

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-22628
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
	8. FARM OR LEASE NAME
1. oil gas well other	9. WELL NO.
2. NAME OF OPERATOR OCT 2 5 1978	1
Exxon Corporation V  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Wildcat
P. O. Box 1600 ATTESIA. OFFICE	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 30, T-26S, R-26E
AT SURFACE: 1880' FSL & 825' FWL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	30-015-22460 15. ELEVATIONS (SHOW DF, KDB, AND WD)
	Takan PA
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	CEIVED
TEST WATER SHUT-OFF	TVEN
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report (Pay) its of multiple cold (Page) or zone change A Fair (Pass).
PULL OR ALTER CASING	change of Fair (9-330.)
MULTIPLE COMPLETE : : : : : : : : : : : : : : : : : :	MA NOW SIDO
ABANDON*	MEXICAL
(other) Change Plans	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is directly measured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and to this work.)*
An extra string of casing will be run as a resin the hole. The hole was sidetracked at 10,3 approximately 11,070' where 7 5/8" liner will 4,500'. The 7 5/8" liner will be 26.4# S-95 Happroximately 11,070' to approximately 7,800' thread to approximately 4,500'. Should it be pipe, it will be the same quality or better.	be set back to approximately lydril SFJP thread from and 39# S-95 Hydril SFJP
It is now proposed to drill to 13,800' in the as originally planned. The 5" casing is to be be 15 and 18# cemented with 500 ± sacks.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Melba Kniplingitle Provation Spec	ialisa <sub>te</sub> October 17, 1978
APPROVED BY APPROVED BY APPROVED BY	
CONDITIONS OF APPROVAL, IF ANY:	DATE
	医二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基