

NM OIL CONS. COMMISSION

Drawer DD

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other PXA

2. NAME OF OPERATOR
Amoco Production Company ✓

3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2080' FSL X 660' FEL, Sec. 29
AT TOP PROD. INTERVAL: (Unit I, NE/4, SE/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-20370
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME RECEIVED
8. FARM OR LEASE NAME
Federal AZ DEC 16 1982
9. WELL NO.
1 O. C. D.
10. FIELD OR WILDCAT NAME
Wildcat Delaware
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
29-26-30
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
2980.6' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Propose to plug and abandon the subject well per the following:

Move in service unit and kill well with 10# brine water. Pull tubing and packer. Packer is set at 3308'. Estimated BHP 1655 psi. Run in hole with cast iron bridge plug and set at 3300'. Cap with 100' of class "C" neat cement thru tubing to seal off Delaware perms 3350'-3396' (32 sx cement). Circulate hole with mud. Spot a 100' plug from 1000'-900 (approx. 32 sx class C cement.) Spot 100' surface plug of class C cement. Cap well and Erect permanent PXA marker. Clean location.

0+4-MMS, R 1-HOU 1-CMH 1-W. Stafford, HOU

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles M. Herring TITLE Ast. Adm. Analyst DATE 12-9-82

APPROVED

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

DEC 15 1982

FOR
JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side