

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Pogo Producing Company

3. ADDRESS OF OPERATOR
P.O. Box 10340 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FSL & 840' FWL
AT TOP PROD. INTERVAL: 990' FSL & 840' FWL
AT TOTAL DEPTH: 990' FSL & 840' FWL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

(other) *Corrected elevations

RECEIVED
MAY 7 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/26/81: TD 2678' Well not commercial, prepare to abandon. Mud salt water gel, wt 10#. RIH to 2678'. Spotted 5 Class C plugs as follows:

Plug No.	No. Sacks	Spotting Depth, Ft.		Formation
		From	To	
1	80	2350'	2678'	Base of Salt to TD
2	35	1790'	1890'	Top of Salt Section
3	105	760'	1120'	Anhydrite
4	40	175'	275'	50' each inside & outside 5 1/2" casing.
5	15	11'	50'	Ground level

(see reverse side)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED B. Williams TITLE Div. Oper. Mgr. DATE May 1, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

SEP 8 1982

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

- Cont. -

Full returns while cementing. Cut off casing flange. Weld on steel plate & install dry hole marker. Released Halliburton at 4:00 pm MDT 4-26-81. Plugging witness by Mr. James Brasfield, Inspector, Oil and Gas Operations, U.S.G.S. Left 213' 8 5/8" 24# K-55 ST&C casing in hole.

Formation	Depth	Datum, Ft.
Quaternary Sand & Gravel	Surface	+2911
Triassic Red Bed	583'	+2337
Rustler Anhydrite	816'	+2104
Salado	1890'	+1030
Lamar Limestone	2590'	+ 329
Bell Canyon	2623'	+ 297