

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT


SUBMIT IN TRIP  
(Other instruction  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. NAME OF OPERATOR  
Wood & Locker, Inc.  
3. ADDRESS OF OPERATOR  
505 N. Big Spring, Suite 600, Midland, Texas 79701  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface  
660' FNL & 990' FEL of Sec. 26, T25S, R27E, Eddy County,  
New Mexico



5. LEASE DESIGNATION AND SERIAL NO.  
NM-13989  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
---  
7. UNIT AGREEMENT NAME  
---  
8. FARM OR LEASE NAME  
Amoco Federal  
9. WELL NO.  
1  
10. FIELD AND POOL, OR WILDCAT  
North Hay Hollow - Bone  
Springs Pool  
11. SEC., T., R., M., OR BLK. AND  
SUBDIVISION OR AREA  
Sec. 26, T25S, R27E  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
New Mexico

14. PERMIT NO.  
15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3087' KB, 3075' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETION ☐  
ABANDON\* ☒  
CHANGE PLANS ☐

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

PLUG NO. 1 - Cast iron bridge plug set at 5860' RKB inside 4-1/2", 11.60# casing and capped with 35' cement.

Cut and pull 4-1/2" casing from 3550' RKB.

PLUG NO. 2 - 35 sacks Class "C" with 2% calcium chloride in and out of 4-1/2" stub from 3550' to 3376' RKB (100' minimum requirement). WOC 2 hrs. Tag top of cement.

PLUG NO. 3 - 35 sacks Class "C" with 2% calcium chloride across 8-5/8" shoe from 2364' to 2232' RKB (100' minimum requirement). WOC 2 hrs. Tag top of cement.

PLUG NO. 4 - 35 sacks Class "C" across "Top of Salt @ 625'" from 675' to 546' RKB.

PLUG NO. 5 - 15 sacks Class "C" surface plug from 70' RKB to 3' BGL. Weld 1/2" steel plate on 16" casing and install dry hole marker, 10.0 ppg salt gel mud between plugs.

18. I hereby certify that the foregoing is true and correct

SIGNED D. M. Johnson TITLE President DATE 5-12-86

(This space for Federal or State office use)

APPROVED BY Area Manager TITLE Area Manager DATE 5-14-86  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side