

Form 3160-5
(September 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
Design Bureau No. 100A-0135
Expires September 30, 1993

3. Lease Description and Serial No.
LG-5340

4. U. S. Name, Address or Title Name

5. U. S. or CA. Agreement Description

6. Well Name and No.
OB #5

7. API Well No.

8. Field and Pool or Supplementary Area
Wsh. Rnch Mor.

9. County or Parish, State
Eddy Co., N.M.

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other

Gas storage Well

2. Name of Operator

El Paso Natural Gas Co.

3. Address and Telephone No.

P.O. Box 1492, El Paso, Texas 79978 (915) 541-2600

4. Location of Well (Permit, Sec., T., R., M., or Survey Description)

2310' FNL & 660' FEL
SEC. 32, T-25-S, R-24-E

CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Cement Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Standard Production
☐ Water Shut-Off
☐ Conversion to Injection

Plug & Abandon

(Note: Report results of multiple completions on Well Completion or Recompletion Report and Log form.)

10. Describe Proposed or Completed Operations (Clarify with all pertinent details and give pertinent data, including estimated date of starting any proposed work. If well is permanently closed, give substantial reasons and measures and give vertical depths for all barriers and other pertinent to the work.)

Page 2 of 2

- 11) RIH w/ Perf. Gun & Perf. 2 holes (.5" dia.-180 phase-2 SPF) @ 1500'. POOH w/ Gun & RD WL.
- 12) RIH w/ Cement Retainer on 2 7/8" Workstring & set @ approx. 1470'. Open WH 7" x 9 5/8" valve.
- 13) RU Western & squeeze/circ. cement (approx. 15 #/gal. Class H) to surface through 7" x 9 5/8" annulus. Close WH 7" x 9 5/8" valve.
- 14) Stingout of Retainer & spot approx. 120' cement above retainer.
- 15) POOH w/ all except 2 Jts. of 2 7/8" Tbg.
- 16) Spot 50' cement surface plug.
- 17) RD Western & PU.
- 18) RU Welder & set Wellbore Marker.

Reservoir Engineer

10/22/92

11. I hereby certify that the foregoing is true and correct

Dave Brewster

Title

Date