

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

NM OIL CONS. COM. 67
SUBMIT IN TRIPLICATE
Draw to other instructions on re-
verse side
Alvordia, NM 88210

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. NAME OF OPERATOR
Callaway Oil & Gas Co.

3. ADDRESS OF OPERATOR
205 Wilco Building, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1780' FNL & 1980' FWL of Section 25.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
2930.8

5. LEASE DESIGNATION AND SERIAL NO.
NM-14478

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mobil - Federal

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 25, T-26-S, R-28-E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) Spudding and set casing ☒
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-29-81: Spudded 12-1/4" hole at 10:00 PM. Kenia Rig #10.

12-30-81: Drilled to a depth of 546'. Ran 8-5/8" casing, 24#/ft., J-55, ST&C, Casing set at 537.74'.

12-31-81: Cemented 8-5/8" casing with 325 sacks Class "C" 2% CACL2. Mixed and pumped at 14.8#/gallon wieght, 1.32 cu.ft./sk yield. Circulate 25 sacks to reserve pit. Bumped plug at 3:30 AM 12-31-81, with 300 psig.

1-6-82: Presently drilling at 3040' in Sand, Anh, and Lime. Deviation survey at 2814' 2°.

RECEIVED
JAN - 7 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Sheryl L. Cook

TITLE Engineering Secretary DATE 1/6/82

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

JAN 11 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side