

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYNM OIL CONS. COMMISSION
NM 22207
Artesia, NM 88210

RECEIVED

APR 2 1982

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ Storage
2. NAME OF OPERATOR
El Paso Natural Gas Company ✓
3. ADDRESS OF OPERATOR
1800 Wilco Bldg. - Midland, Texas 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2736' FSL & 1602 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

Spud & Drlg Operations

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Washington Ranch Storage Project

9. WELL NO.

WI-Federal #20

10. FIELD OR WILDCAT NAME

Washington Ranch

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 34, T-25-S, R-24-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GR 3715.0'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12 1/4" hole on 2/14/82 @ 12/15 AM, Young Drlg Rig No. 4. Drilled to 835' and ran 9 5/8", 32.3#, H-40 casing set @ 814.59'. Cemented w/500 sx C1 "C" and cemented backside thru 1" tubing w/ 668 sx C1 "C". Job complete 1:45 PM, 2-16-82. Top of cement @ surface. WOC 17 1/4 hrs and tested casing, test OK. Reduced hole to 8 3/4" and drilled to 7,000' and ran 7", 23#, N-80 casing set @ 6,984.87'. Cement with 500 sx C1 "H" cement. Job complete @ 3:15 PM, 3-6-82. Top of cement at 5,400'. Released rig 3/6/82 and waiting on completion.

Project Approved by NMOCD Order No. R-6175-A

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

John P. Seick

TITLE Suprv. Prod. Svcs. DATE March 12, 1982

FOR RECORD

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

MAR 19 1982

TITLE

DATE

U.S. GEOLOGICAL SURVEY
NEW MEXICO

*See Instructions on Reverse Side