Form 9-331 Dec. 1973

UNITED STATES DEPARTMENT OF THE INTERIOR

<u></u>					
		•	•	Form Approved. Budget Bureau	
	5	LEASE			10. 42-1(1424
		<u>IM-16131</u>			
				TTEE OR TRIB	531445
_	٠.	יייייייייייייייייייייייייייייייייייייי	ALLC	TILE OR INIB	ENAME
	7.	UNIT AGRI	FFMF	NT NAME	
t	8. FARM OR LEASE NAME Federal DB				
11.					
٠.					
		WELL NO.	טט		·
		ן			
_	10,	FIELD OR	WILD	CAT NAME	<del></del>
		<del>nd</del> . Mor	row		
_	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
<b>'</b>	AREA				
	12	22-2			
				RISH 13. STA	TE
		ddy		NM.	
-	14. API NO.				
'	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
	15.			HOW DF, KDB	, AND WD)
ı		3348	3		
	40.00				
(NOTE: Report results of multiple completion or zone change on Form 9-330.)					
	5				

**GEOLOGICAL SURVEY** SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to draff or to deepen RECEIVED a different reservoir. Use Form 9–331–C for such proposals.) 1. oil X  $\sqcup$ weli well 2. NAME OF OPERATOR Amoco Production Company 3. ADDRESS OF OPERATOR RTESIA, OFFICE 88240 P. O. Box 68, Hobbs, NM 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1980' FSL X 1980' FEL, Sec. 22 AT TOP PROD. INTERVAL: (Unit J, NW/4,SE/4) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON\* Spud (other) DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* On 6-26-82 McVay #10 spudded a 20" hole and drilled to TD of 417'. 16" 65 lb/ft. casing set at 417'. Cemented with 475 sacks class C with .3% Halad 4. Cement did not circulate. Brought cement to surface (from 6' below cellar) with ready mix. WOC 18 hours. Tested casing to 600 PSI for 30 min. Tested O.K. Reduced bit to 14-3/4" and resumed drilling. 0+6-USGS,R 1-HOU 1-DMF 1-W. STAFFORD, HOU \_ Set @ \_\_

Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED TITLE Ast. Adm. Analyst DATE FOR RECORDThis space for Federal or State office use) APPROVED B DATE CONDITIONS OF APPROVAL, IF OCT ROSWELL, NEW MEXICO