

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Draper 00
Artesia, NM 88110

5. LEASE
NM-28172

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Delta Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME
Wildcat (Morrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 7, T25S, R26E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3413.8 GR

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐ OCT 1982

2. NAME OF OPERATOR
THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. Box 3901, Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL, 660' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON ☐

(other) Weekly Drilling Report & Casing Detail

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9-18-82 Svy @ 9100' = no good.

9-19-82 Svy @ 9100' = 2 1/4". RU csg crews. Running 7 5/8" csg.

9-20-82 Run 7 5/8" csg - DL float shoe - 2 jts 7 5/8" 33.70 S-95 LT&C - DL float collar - 20 jts 33.70 S-95 LT&C - 110 jts 29.70 S-95 LT&C - 95 jts 7 5/8" 26.40 S-95 LT&C. Total 227 jts OAL 9133'. Ran to depth of 9100'. RU Hughes. Cmtg. lead slurry - 500 gal RJ mud sweep - 850 sks Class H w/additives. WOC in excess of 24 hrs.

9-21-82 Testing BOP's. WOC.

9-22-82 Drlg out plug - float collar - 105' cmt - float shoe. Drlg to 9375'.

9-23-82 Svy @ 9633' = 2". Drlg to 9705'.

9-24-82 Drlg to 9992'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Prod. Supt. DATE 9-24-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side