

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
JUN 29 1983

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other DRILLING WELL
2. NAME OF OPERATOR
WORTH PETROLEUM COMPANY
3. ADDRESS OF OPERATOR
P.O. BOX 17406, FORT WORTH, TEXAS 76102
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1900' FNL & 330' FEL OF SECTION 29
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) SET SURFACE CASING.	PROGRESS REPORT.

5. LEASE NM-38636
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME AMOCO FEDERAL
9. WELL NO. 2
10. FIELD OR WILDCAT NAME WILDCAT Cherry Canyon
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 29, T. 26 S., R. 29 E.
12. COUNTY OR PARISH EDDY 13. STATE NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 2873 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-8-83: Spudded well.

Drilled 12-1/4" hole to depth of 455 feet. Set 8-5/8" casing at 452 feet with 450 sacks of Class "C" cement. Cement circulated.

5-25-83: Reached depth of 5344 feet, at which time bottom joint of surface casing came off and dropped to 496 feet. Milled and reamed on joint of casing but could not get through it or past it.

5-31-83: Preparing to plug and abandon.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Arthur R. Brown TITLE Agent DATE 6-6-83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

RSP
JUN 27 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO